

Technical data magazine ads sheet-fed press

Printing process:

Sheet-fed offset press

Graphic processing:

Please convert the optimised RGB images into CMYK by using the included ICC profile: **ISO Coated v2 (ECI).icc**

Resolution: 300 dpi

Maximum ink coverage: 340%

If there is no white border: the distance from trim edge to texts and logos should be at least 7 mm.

All PDF files must meet the Medibel+ requirements (MagazineAds_1v2)

- We only accept 'composite PDF 1.3'. We do not accept PDF 1.4, 1.5 or 1.6, transparency, JBIG-compression, JPEG 2000-compressions, images with 16 bits per channel and layers.
- Please enclose all the used fonts in the PDF file.
- If you use spot colors, please convert them to CMYK colors before creating the PDF file.
- The PDF file format must be the document format + 20 mm
(this means a bleed of 5 mm + 5 mm extra around the document).

For more information, visit www.medibelplus.be.

Naming:

Please use letters and numbers only, no punctuation marks nor spaces.

Please send the file by:

uploading it on our FTP server: <ftp://bblg.boerenbond.be>, user: msdrop, password: Keiðieih

sending an e-mail to: info@mediaservice.be (please make sure the file is not bigger than 8 MB)

using We Transfer: boerenbond.wetransfer.com

Correspondence:

Boerenbond-Mediaservice, Diestsevest 40, 3000 Leuven, T 016 28 63 33

Please notify Mediaservice at info@mediaservice.be when supplying digital materials.